

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

(11) Publication number:

**0 359 831  
A1**

(12)

**EUROPEAN PATENT APPLICATION  
published in accordance with Art.  
158(3) EPC**

(21) Application number: 89904212.1

(51) Int. Cl.<sup>5</sup>: **G01N 27/28 , G01N 27/30**

(22) Date of filing: 30.03.89

(86) International application number:  
**PCT/JP89/00337**

(87) International publication number:  
**WO 89/09397 (05.10.89 89/24)**

(30) Priority: 31.03.88 JP 80829/88  
31.03.88 JP 80842/88  
18.05.88 JP 121002/88

(43) Date of publication of application:  
**28.03.90 Bulletin 90/13**

(84) Designated Contracting States:  
**DE FR GB IT**

(71) Applicant: **Matsushita Electric Industrial Co., Ltd.**  
**1006, Oaza Kadoma**  
**Kadoma-shi Osaka-fu, 571(JP)**

(72) Inventor: **NANKAI, Shiro**  
**50-12, Nasuzukuri 4-chome**  
**Hirakata-shi Osaka 573(JP)**  
Inventor: **KAWAGURI, Mariko**  
**Thowamoriguchihaun 202 12-1,**  
**Dainichicho**  
**1-chome Moriguchi-shi Osaka 570(JP)**  
Inventor: **FUJITA, Mayumi**  
**131-85, Kajimachi 3-chome**  
**Moriguchi-shi Osaka 570(JP)**  
Inventor: **IJIMA, Takashi**  
**35-26, Yamanouenishimachi**  
**Hirakata-shi Osaka 573(JP)**

(74) Representative: **Graf von Wengersky, Anton et al**  
**Patentanwälte Leinweber & Zimmermann**  
**Rosental 7**  
**D-8000 München 2(DE)**

**EP 0 359 831 A1**

(54) **BIOSENSOR AND PROCESS FOR ITS PRODUCTION.**

(57) A biosensor of the invention comprises an insulating base board (1) having formed thereon, in sequence, leads (2, 3, 3'), an electrode system mainly made of carbon (4, 5, 5'), an insulating layer (6) and a reaction layer (14) composed of an enzyme and an electron acceptor, and being provided thereon with a space (8) defined by a spacer (7) and a cover (9). When a biological sample solution is

brought into contact with the inlet (10) of the biosensor having the above-described structure, the sample solution is introduced into its inside, while the air within the space (8) is rapidly discharged through the outlet (11) and, at the same time, the space (8) is filled with the sample solution up to the neighborhood of the outlet. Thus, measurement can be conducted inexpensively at a high speed with a high